U.S. DEPARTMENT OF LABOR Occupational Safety and Health Administration

Form Approved OMB No. 44-R1387

MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

SECTION I						
MANUFACTURER'S NAME	EMERGENCY TELEPHONE NO.					
GROW CHEMICAL SEALANTS CORPORATION	(213) 269-0461					
ADDRESS (Number, Street, City, State, and ZIP Code) 3137 East 26th Street., Los Angeles, Californi	a 90023					
CHEMICAL NAME AND SYNONYMS TRADE NO GC-40	ME AND SYNONYMS					
Polysulfide HS-R-SH						

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS	25		BASE METAL		
CATALYST	5		ALLOYS ,		
VEHICLE	70		METALLIC COATINGS		
SOLVENTS	0		FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES Less than	3		OTHERS		
OTHERS					
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES					TLV (Units
					<u> </u>

SECTION III - PHYSICAL DATA					
BOILING POINT (°F.)	N.A.	SPECIFIC GRAVITY (H2O=1)	1.5		
VAPOR PRESSURE (mm Hg.)	N.A.	PERCENT, VOLATILE Less than	.2		
VAPOR DENSITY (AIR=1)	N.A.	EVAPORATION RATE (=1)	N.A.		
SOLUBILITY IN WATER	No				
APPEARANCE AND ODOR Off whi	te to gray	semi-solid			

SECTION IV - FIRE AND EXPLOSION HAZARD DATA							
Open cup greater than 400°F	FLAMMABLE LIMITS N.A.	Lel	Uei				
Extinguishing Media Water, CO ₂ , foam, dry chemicals							
SPECIAL FIRE FIGHTING PROCEDURES							
None							
UNUSUAL FIRE AND EXPLOSION HAZARDS							
None							

PAGE (1)

(Continued on reverse side)

Form OSHA-20 Rev. May 72

SECTION V - HEALTH HAZARD DATA
THRESHOLD LIMIT VALUE Ingestion 0.5-5 gr/kilo .
EFFECTS OF OVEREXPOSURE May cause skin or eye irritation upon contact.
EMERGENCY AND FIRST AID PROCEDURES Wash hands thoroughly. Flush eyes
copiously with water. Give emetic if ingested

			SECTION	אע VI - R	EACTIVITY DATA	
STABILITY	UNS	UNSTABLE		CONDITIONS TO, AVOID		
	STAE	BLE .	X	Store	e below 80°F	
INCOMPATABIL	ATY (Mater	ials to avoid;		•		
HAZARDOUS D		tion production pases ar		idizing	agents .	
HAZARDOUS	ous MAY OCCUR			CONDITIONS TO AVOID		
POLYMERIZATI	ON	WILL NOT OCCUR		X		

SECTION VII - SPILL OR LEAK PROCEDURES	
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED	
Scrape up and clean with ketones or toluene.	
WASTE DISPOSAL METHOD	
Normal non-hazardous trash disposal.	

	SECTION VIII - SPECIA	AL PROTECTION INFORMATION
RESPIRATORY P	ROTECTION (Specify type) Non	ne required
VENTILATION	LOCAL EXHAUST Sufficient	SPECIAL
•	MECHANICAL (General)	OTHER
PROTECTIVE GLO		EYE PROTECTION
	Recommended	Recommended
OTHER PROTECT	ive equipment none	

SECTION IX - SPECIAL PRECAUTIONS					
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING Wash hands thoroughly after					
handling. Do not ingest. Store indoors below 80°F					
None					

PAGE (2)

GPO 934-110

Form OSHA-20 Rev. May 72